

pH 7 Vio portable pH meter without electrode

Code: 50110022



DATA SHEET

Regulations

Regulations	CE
-------------	----

Performance

Accuracy (pH)	± 0,02
Accuracy (Temperature)	± 0,5 °C
mv measuring range (max.)	+ 1000
mv measuring range (min.)	- 1000
ORP measuring range (max.)	+ 1000
ORP measuring range (min.)	- 1000
ORP resolution	1 mV
pH measuring range (max.)	+ 14,00
pH measuring range (min.)	0
pH resolution	0,01
Temperature compensation	0,0...100,0 °C
Temperature measuring range (max.)	+ 100,0 °C
Temperature measuring range (min.)	0,0 °C
Temperature resolution	0,1 °C
Working temperature (max.)	+ 45 °C
Working temperature (min.)	0 °C

Feature

Calibration report	Yes
DHS compatible	Yes
Display	Backlight coloured high definition LCD
Inputs	BNC - RCA
IP protection	IP 57
Points of calibration ORP	1
Points of calibration pH	1...3 auto / 2 custom values
Stability criteria	3 levels
Standard approved pH	USA - NIST

Supply

Power supply	3 batteries AA 1,5 V
--------------	----------------------

Dimension and Weight

Dimension (LxWxH)	185 x 85 x 45 mm
Weight	400 g